



IMPORTED BEARING OF AMERICA CORP.



200 mm x 420 mm x 80 mm 200 mm x 420 mm
x 80 mm KOYO NU340 cylindrical roller bearings

Bearing No. NU340

| | |
|-------------------------------|---------------|
| Size | 200x420x80 mm |
| Bore Diameter | 200 mm |
| Outer Diameter | 420 mm |
| Width | 80 mm |
| d | 200 mm |
| Fw | 260 mm |
| D | 420 mm |
| B | 80 mm |
| C | 80 mm |
| r min. | 5 mm |
| r1 min. | 5 mm |
| Weight | 56.2 Kg |
| Basic dynamic load rating (C) | 987 kN |
| Basic static load rating (C0) | 1270 kN |
| (Grease) Lubrication Speed | 1200 r/min |
| Bearing No. | NU340 |
| r(min) | 5 |
| r1(min) | 5 |
| Cr | 1220 |
| C0r | 1270 |
| Cu | 145 |
| Grease lub. | 1200 |
| Oil lub. | 1700 |
| Ew | - |
| d1 | - |

NU340 Bearing 2D drawings and 3D CAD models



IMPORTED BEARING OF AMERICA CORP.

| | |
|------------------|------|
| B1 | - |
| B2 | - |
| da(min) | - |
| db(min) | 220 |
| db(max) | 254 |
| dc(min) | - |
| dd(min) | - |
| Da(max) | 400 |
| Db(max) | - |
| Db(min) | - |
| ra(max) | 4 |
| rb(max) | 4 |
| (Refer.)Mass(kg) | 56.2 |